

emco Bau

emco DIPLOMAT Original SPIN®Safe With ribbed carpet insert 22 SPIN /R

Model	22 SPIN/R
Load	Normal to heavy
Support chassis	Reinforced support chassis made using rigid aluminium with sound absorbing insulation on the underside
Approx. height (mm)	25.9
Tread surface	Recessed, robust, weather-proof coarse-fibre ribbed carpet strips (brand-name fibres) for even better dirt removal. Combined with stainless steel tiles for optimum way guidance for the blind in the entrance area.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Slip resistance	Slip-resistance of the insert: R11, slip-resistance of the stainless steel tiles: R9 (in accordance with DIN 51130)
Colours	Anthracite no. 200
Connection	Plastic-coated steel cable
Warranty	4 year warranty
	Warranty conditions are available at:
Colour fastness to artificial light ISO 105-B02	good 6
Colour fastness to rubbing ISO 105 X12	good 4
Colour fastness to water ISO 105 E01	good 5
Dimensions	Mat width:mm (bar length)
	Mat depth:mm (walking direction)
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D- 49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140- 500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com