

## emco Bau

### emco MARSCHALL Original With ribbed carpet insert 522 TLS SR

<b>Model</b>	522 TLS SR
<b>Load</b>	Extremely heavy
<b>Support chassis</b>	made of rigid aluminium with sound insulation underlay. In the area of the tactile guidance system, the profiles are laid alternately in two heights.
<b>Approx. height (mm)</b>	22
<b>Tread surface</b>	Recessed, robust, weather-proof coarse fibre ribbed carpet strips (brand-name fibres) for even better dirt removal.
<b>Standard profile clearance approx. (mm)</b>	3 mm, rubber spacers
<b>Colours</b>	Anthracite no. 200 Light grey no. 220
<b>Connection</b>	With threaded rod
<b>Warranty</b>	4 year warranty
<b>Pile material</b>	100% PP (polypropylene)
<b>Colour fastness to artificial light ISO 105-B02</b>	good 6
<b>Colour fastness to rubbing ISO 105 X12</b>	good 4
<b>Colour fastness to water ISO 105 E01</b>	good 5
<b>Dimensions</b>	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
<b>Contact</b>	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com