

## emco Bau

### Clean-off system INNOVA TILES

|                                                        |                                                                                                                                                                                                                      |
|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                                           | INNOVA TILES<br>For laying indoors                                                                                                                                                                                   |
| <b>Construction</b>                                    | Tufting velour 5/32"                                                                                                                                                                                                 |
| <b>Pile above substrate</b>                            | 100% polyamide                                                                                                                                                                                                       |
| <b>Substrate material</b>                              | Polyester fleece                                                                                                                                                                                                     |
| <b>Backing material</b>                                | Bitumen                                                                                                                                                                                                              |
| <b>Pile weight / fibre weight</b>                      | 850 g/m <sup>2</sup>                                                                                                                                                                                                 |
| <b>Total weight (g/m<sup>2</sup>)</b>                  | 3930 g/m <sup>2</sup>                                                                                                                                                                                                |
| <b>Overall height (mm)</b>                             | 8 mm                                                                                                                                                                                                                 |
| <b>Combustion/fire behaviour</b>                       | Bfl-s1                                                                                                                                                                                                               |
| <b>Slip resistance</b>                                 | DS (EN 13893)                                                                                                                                                                                                        |
| <b>Certificates</b>                                    | CE conformity EN 14041 (rolls only)                                                                                                                                                                                  |
| <b>Colours</b>                                         | 36.01 black<br>36.02 anthracite<br>36.03 grey<br>36.08 mocha<br>36.10 slate                                                                                                                                          |
| <b>Colour fastness to artificial light ISO 105-B02</b> | ≥5                                                                                                                                                                                                                   |
| <b>Colour fastness to rubbing ISO 105 X12</b>          | ≥4                                                                                                                                                                                                                   |
| <b>Colour fastness to water ISO 105 E01</b>            | ≥4                                                                                                                                                                                                                   |
| <b>Supplied as tiles</b>                               | approx. 50 x 50 cm without a border (with asphalt coating)                                                                                                                                                           |
| <b>Product characteristics</b>                         | Soiling and moisture absorption                                                                                                                                                                                      |
| <b>Brand</b>                                           | emco                                                                                                                                                                                                                 |
| <b>Contact</b>                                         | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · <a href="http://www.emco-bau.com">www.emco-bau.com</a> |